

TINT SEAL

REJUVENATE YOUR WORN OUT PAVERS!







Mix Ratio: 3 oz

Mix Ratio : 6 oz

Mix Ratio : 9 oz

**AVAILABLE IN THE
FOLLOWING
COLORS:**

-  **CHARCOAL
GREY**
-  **SLATE GREY**
-  **SANDSTONE**
-  **CORDOVA
BROWN**
-  **MOROCCO
RED**

-  **CHANGE OR ENHANCE
COLORS**
-  **RETAIN NATURAL PAVER
LOOK**
-  **UV-RESISTANT SYSTEM**
-  **ONE-PART URETHANE
BASE**

Tint-Seal Instructions

**In addition to completing the following preparatory work, ensure there are no additional sealers on the surface to promote proper absorption of Tint-Seal.*

1. Check the surface of the pavers for any existing sealer. If the surface contains an existing sealer, strip with ColorBack Horizontal Hard Surface Stripper.
2. Clean the surface using standard paver cleaning practices.
3. Allow pavers to become surface dry before applying Tint-Seal. For the best results, do not apply Tint-Seal to a wet or damp surface. Dry times vary depending on air temperature, wind, and humidity.
4. Mix the dedicated tint package in the sealer for two (2) minutes directly before use. Stir occasionally to ensure color uniformity.
5. To achieve the best results, we recommend applying Tint-Seal with an airless sprayer. Recommended tip size: .013 - .015. Recommended pressure: Low - Medium. If a pump sprayer is being used, ensure that it reaches full atomization to prevent puddling or over application. It is important that the machine can produce an even, consistent fan and complete full courses.
6. Begin at the top or bottom of the desired area and spray full courses from one side to the other achieving a 50% wet-on-wet overlap on each pass. If you must stop spraying before the entire area is covered, stop on a joint line.
7. If additional color is desired. Apply a second coat after two (2) hours.

SCAN QR CODE TO VIEW PROPER SPRAYING TECHNIQUE



TINT MIX RATIO

(Per 5 Gallons of Sealer)

**MIX IN SEALER FOR TWO (2) MINUTES
DIRECTLY BEFORE USE**

3 OZ - TONING

6 OZ - SEMI-TRANSPARENT

9 OZ - FULL COVERAGE

CAUTION

**HARMFUL IF SWALLOWED.
MAY CAUSE EYE, SKIN, AND RESPIRATORY IRRITATION
KEEP OUT OF REACH OF CHILDREN**

acrylux
100% acrylic

6010 POWERLINE ROAD FORT LAUDERDALE, FL 33309
WWW.ACRYLUX.COM