



6010 N. Powerline Road, Ft. Lauderdale, FL 33309  
954-772-0300 • acrylux.com

## PRODUCT DATA

### **507B SEMI-GLOSS**

- PRODUCT NAME:** Acrylux 507B Semi-Gloss
- PRODUCT NUMBERS:** 507B5, 507B1, 507BWC5, 507BWC1, DTG5, DTG1
- DESCRIPTION:** A heavy body, 100% Acrylic Latex wall and trim paint.
- SUGGESTED USES:** A semi-gloss finish coat for exterior masonry, stucco, wood, brick, cement tile, aluminum, primed metal and all previously painted surfaces.
- COLORS:** Bright white, pearl white, and bases for 3000 custom colors.
- FINISH:** Semi-Gloss
- VEHICLE TYPE:** Spherical and lobed acrylic polymer
- SOLVENT TYPE:** Water
- VOC:** gm/l 303
- FLASH POINT:** Non-flammable
- SOLIDS BY VOLUME:** 36.91 %
- SOLIDS BY WEIGHT:** 48.28 %
- WEIGHT PER GALLON:** 10 lbs. 9 oz
- RECOMMENDED WET FILM:** 2– 3mils
- RECOMMENDED DRY FILM:** 2– 2.5 mils
- COVERAGE:** Theoretical coverage at 3mils is 250 sq. ft per gallon. Material losses during application and surface porosity will vary and must be taken into consideration when estimating job requirements.
- VISCOSITY:** 82 to 84 ku
- RECOMMENDED DRY TIME:** 1 to 2 hours in direct sunlight; dry times may vary depending on air temperature, wind, and humidity.
- LIMITATIONS:** Not for use under ponding water or below grade applications.
- RECOMMENDED PRIMERS:** Acrylux AC64, Acrylux UL200, Emulsa-Bond, or any high quality latex or alkyd primer.

**FPL APPROVED – ENERGY STAR PARTNER**