

ACRYGLAZE-UV

A protective UV inhibitive sealer for roof tiles and shingles that is designed to keep your cement tile roof looking clean and new by reducing ultraviolet fading, water degradation and mildew formation. Acryglaze-UV retards fungus and mildew development for up to five years. Only one coat of Acryglaze-UV is required where most other sealers demand two or more coats.

- APPLICATION:**
- Apply one thorough, even coat. Once Acryglaze-UV dries it can be recoated in order to achieve a higher sheen.
 - Apply with a brush, medium roller, or sprayer (hand pump or airless)
 - Apply from the top down on most roofs, taking care not to puddle because of over application.

- DRY TIMES:**
- Dry to the touch: 30 to 60 minutes
 - Full cure: 24 hours
 - Recoat: 2 to 4 hours

- PREPARATION:**
- For new concrete tiles, no special preparation is necessary other than making sure the surface is free from waxes, mold release chemicals, moisture or efflorescence that may inhibit penetration of Acryglaze-UV.
 - For older concrete tiles, pressure clean thoroughly to remove dirt, mildew, algae and any other contaminants. All surfaces must be clean, sound and dry before application.

- ACRYLUX ADVANTAGE:**
- Acryglaze-UV reacts and cross-links with concrete to form a more waterproof substrate. It will not wash away like water sealers.
 - Stops efflorescence from occurring and spoiling the look of colored roof tiles. Because no water can get into the substrate, no salts, or pigments can leach out and cause a "whitish," washed-out look.
 - Retards mold and mildew from forming on roof tiles because of high levels of biocides as well as sealing properties. Mildew cannot attach itself and begin to grow.
 - Keeps roof tiles from getting dirty because Acryglaze-UV fills the pores in which dirt may attach itself. Sealed concrete tiles will then provide some self-cleaning with wind and rain.

- TECHNICAL DATA:**
- | | | | |
|-------------|------------------|---------------------|---------------------|
| • Coverage: | 200 sq. ft./gal. | • Appearance: | White, milky liquid |
| • Solids: | 37.4% | • Light Stability: | Excellent |
| • Clean-Up: | Water | • Durability: | Excellent |
| • VOC: | None | • Water Resistance: | Excellent |

- LIMITATION OF LIABILITY:**
- Acrylux Paint Manufacturing Co. warrants that if any goods supplied prove defective in workmanship or material, that Acrylux shall replace them or refund their purchase price. Before application the user shall determine the appropriate use of this product and the user assumes all risks and liabilities whatsoever in connection therewith. The sole liability of Acrylux for any claims arising out of the use or sale of this product shall be for the user's purchase price.