



6010 N. Powerline Road, Ft. Lauderdale, FL 33309
954-772-0300 • acrylux.com

PRODUCT DATA

ELASTO-FILL

PRODUCT NAME:	Acrylux Elasto-Fill
PRODUCT NUMBERS:	EF5
DESCRIPTION:	A ceramic fortified elastomeric tile filling compound.
SUGGESTED USES:	Use for tile filling cement tile roofs, (filling in the spaces or gaps between cement tiles). Use on flat tile, s-tile, double roll tile, barrel tile, slate tile, shingle and any other cement or asphalt roof that requires gap filling.
COLORS:	Medium Gray
FINISH:	Semi-smooth
VEHICLE TYPE:	Elastomeric / Acrylic
SOLVENT TYPE:	Water
VOC:	< gm/l 75
FLASH POINT:	Non-flammable
WEIGHT PER GALLON:	7.5 lbs.
SPECIFIC GRAVITY:	> 1
THICKNESS:	Butter Grade
COVERAGE:	Varies according to application and crack widths.
VISCOSITY:	> 150 ku
RECOMMENDED DRY TIME:	4 to 6 hours in direct sunlight; dry times may vary depending on air temperature, wind, humidity and applied thickness.
LIMITATIONS:	Not for use under ponding water or below grade applications. Not for rusted surfaces.
SURFACE PREPARATION:	<i>For masonry:</i> Remove all loose paint, dirt, mildew and chalk by high pressure water cleaning or other methods to obtain a sound surface. Unpainted tile or chalky surfaces must be sealed with AC64 primer/sealer.
MIXING:	No mixing necessary.
SHELF LIFE:	2 years