



6010 N. Powerline Road, Ft. Lauderdale, FL 33309  
954-772-0300 • acrylux.com

## PRODUCT DATA

### ***MASONRY PATCH***

- PRODUCT NAME:** Acrylux Masonry Patch
- PRODUCT NUMBERS:** MP1, MP5
- DESCRIPTION:** An elastomeric patching compound.
- SUGGESTED USES:** Hairline cracks, feather edging, and patching small holes.
- COLORS:** Off white
- FINISH:** Sand texture
- VEHICLE TYPE:** Elastomeric
- SOLVENT TYPE:** Water
- VOC:** gm/l 75
- FLASH POINT:** Non-flammable
- WEIGHT PER GALLON:** 12 lbs.
- SPECIFIC GRAVITY:** 1.3
- THICKNESS:** 3/16"
- COVERAGE:** Varies according to application and crack widths.
- VISCOSITY:** Butter grade
- RECOMMENDED DRY TIME:** 4 to 6 hours in direct sunlight; dry times may vary depending on air temperature, wind, and humidity.
- LIMITATIONS:** Not for use under ponding water or below grade applications. Not for rusted surfaces.
- SURFACE PREPARATION:** *For masonry:* Remove all loose paint, dirt, mildew and chalk by high pressure water cleaning or other methods to obtain a sound surface. Seal any remaining chalk with AC64 primer/sealer.
- MIXING:** No mixing necessary.
- APPLICATION:** Brush, knife or trowel.
- SHELF LIFE:** 2 years
- PACKAGING:** 1 gallon, 5 gallon