



6010 N. Powerline Road, Ft. Lauderdale, FL 33309
954-772-0300 • acrylux.com

PRODUCT DATA

ROOF GLOSS

PRODUCT NAME: Acrylux Roof gloss
PRODUCT NUMBERS: RG5, RG1, DTG5, DTG1, DTSG5, DTSG1
DESCRIPTION: A heavy body, 100% Acrylic Latex roof paint.

SUGGESTED USES: A semi-gloss finish coat for a variety of roofs including: cement tile, barrel tile, bermuda, gravel, bahama, aluminum, steel, and asphalt shingle*
**Always apply a test patch to asphalt shingles to check for bleeding of asphalt into paint or curling.*

COLORS: Bright white, pearl white, and bases for 3000 custom colors.

FINISH: Semi-Gloss

VEHICLE TYPE: Spherical and lobed acrylic polymer

SOLVENT TYPE: Water

VOC: gm/l 303

FLASH POINT: Non-flammable

SOLIDS BY VOLUME: 36.91 %

SOLIDS BY WEIGHT: 48.28 %

WEIGHT PER GALLON: 10 lbs. 9 oz

RECOMMENDED WET FILM: 2– 3mils

RECOMMENDED DRY FILM: 2– 2.5 mils

COVERAGE: Coverage depends on surface texture and porosity. Smooth surfaces: 300 sq. ft. per gallon; Textured or Rough surfaces: 250 sq. ft. per gallon; Smooth Flat Roof Tile: 150 sq. ft. per gallon; Broom Swept or Barrel Tile: 100 sq. ft. per gallon.

VISCOSITY: 82 to 84 ku

RECOMMENDED DRY TIME: 1 to 2 hours in direct sunlight; dry times may vary depending on air temperature, wind, and humidity.

LIMITATIONS: Not for use under ponding water or below grade applications.

RECOMMENDED PRIMERS: Acrylux AC64

FPL APPROVED – ENERGY STAR PARTNER

(Roof Gloss Cont'd)

SURFACE PREPARATION: *For concrete tile:* Remove all loose paint, dirt, mildew and chalk by high pressure water cleaning or other methods to obtain a sound surface. Seal any remaining chalk with AC64 primer/sealer. *For metal roofs:* May be applied directly to weathered aluminum and galvanized steel. All other applications to metal require an appropriate primer.

MIXING: Stir well and apply as it comes from the container. Box all colors to insure color uniformity.

APPLICATION: Brush, Roller (min 1" nap), or airless spray. Recommended tip size: .017 to .021.

SHELF LIFE: 2 years

PACKAGING: 1 gallon, 2 gallon, 5 gallon, 55-gallon drum

SPECIFICATIONS:

Titanium	15.0%	Acrylic Resin	27.0%
		Water & Glycols	54.3%
		Additives	3.7%
Pigments	15.0%	Vehicle	85.0% = 100%

SAFETY INFORMATION: Use with adequate ventilation. Do not ingest. Avoid prolonged contact with the skin. Wash immediately after use and before smoking and eating. Avoid breathing vapors and mist. In case of eye contact, flush eyes immediately with water and continue for at least 15 minutes and consult a physician. Close container after each use. Keep out of the reach of children. If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to www.epa.gov/lead.