



6010 N. Powerline Road, Ft. Lauderdale, FL 33309
954-772-0300 • acrylux.com

PRODUCT DATA

WATERPROOFING

PRODUCT NAME: Acrylux Waterproofing

PRODUCT NUMBERS: WP5, WP1, WP55

DESCRIPTION: A liquid applied waterproof coating designed to prevent water intrusion. Waterproofing has a high tack finish, therefore, a finish top coat is recommended.

SUGGESTED USES: Use on cement tile, bermuda tile, barrel tile, shingle*, brick, block, stucco and all masonry surfaces.
**Always apply a test patch to asphalt shingles to check for bleeding of asphalt into coating and possible curling.*

APPLICATION SUBSTRATE: Excellent adhesion to a wide range of roofing substrates including: aged modified bitumen, asphalt shingle, polymer membrane, metal, sprayed polyurethane foam, and cement. (Passes ASTM D-6083)

COLORS: White and pastel to medium colors.

FINISH: Satin-Flat (a low angular sheen)

VEHICLE TYPE: 100% acrylic

SOLVENT TYPE: Water

COATING VOC: 37 G/L

MATERIAL VOC: 21 G/L

FLASH POINT: Non-flammable

TOTAL VEHICLE BY VOLUME: 91.07% **TOTAL VEHICLE BY WEIGHT:** 79.01%

RECOMMENDED WET FILM: 8– 10mils

RECOMMENDED DRY FILM: 6– 8 mils

COVERAGE: Theoretical coverage at 8 mils is 100 sq. ft per gallon. Material losses during application and surface porosity will vary and must be taken into consideration when estimating job requirements.

VISCOSITY: 96 to 102 ku

RECOMMENDED DRY TIME: 2 to 3 hours in direct sunlight; dry times may vary depending on air temperature, wind, and humidity.

LIMITATIONS: Not for use under heavy ponding water or below grade applications.

RECOMMENDED PRIMERS: Acrylux AC64